



MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

Product Name: Cutting Oil Thread Cutting Lubricant (aerosol)

Product Number (s): 14050, 75500

Product Use: Cutting oil

Manufacturer / Supplier Contact Information:

In United States:

CRC Industries, Inc.

885 Louis Drive

Warminster, PA 18974

www.crcindustries.com

1-215-674-4300 (General)

(800) 521-3168 (Technical)

(800) 272-4620 (Customer Service)

In Canada:

CRC Canada Co.

2-1246 Lorimar Drive

Mississauga, Ontario L5S 1R2

www.crc-canada.ca

1-905-670-2291

In Mexico:

CRC Industries Mexico

Av. Benito Juárez 4055 G

Colonia Orquídea

San Luís Potosí, SLP CP 78394

www.crc-mexico.com

52-444-824-1666

24-Hr Emergency – CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

WARNING: Flammable. Contents Under Pressure.

Appearance & Odor: Brown viscous liquid, faint petroleum odor

Potential Health Effects:

ACUTE EFFECTS:

EYE: Eye contact may result in slight irritation and redness.

SKIN: Short term contact with skin is unlikely to cause any problems. Excessive or repeated contact and poor hygiene conditions may result in dryness, dermatitis, erythema, oil acne, cracking and defatting of the skin.

INHALATION: Inhalation of vapors or mist may be irritating to the respiratory passages. Prolonged exposure may result in dizziness and nausea.

INGESTION: May result in nausea or stomach discomfort.

CHRONIC EFFECTS: None known

TARGET ORGANS: Lungs (oil mist)

Medical Conditions Aggravated by Exposure: pre-existing skin disorders

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Name: Cutting Oil Thread Cutting Lubricant (aerosol)

Product Number (s): 14050, 75500

Section 3: Composition/Information on Ingredients

| COMPONENT | CAS NUMBER | % by Wt. |
|-----------------------------|-------------------|-----------------|
| Hydrotreated naphthenic oil | 64742-52-5 | 70 - 80 |
| Additive blend | proprietary | 2 - 6 |
| Liquefied petroleum gas | 68476-86-8 | 15 - 25 |

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

Ingestion: If swallowed, observe for signs of stomach discomfort or nausea. If symptoms persist, seek medical help. Do not induce vomiting. If there is any suspicion of aspiration into lungs, obtain immediate medical attention.

Note to Physicians: Treat symptomatically.

Section 5: Fire-Fighting Measures

Flammable Properties: This product is flammable in accordance with aerosol flammability definitions. (See 16 CFR 1500.3(c)(6)).

Flash Point: > 300°F / 149°C (COC) Upper Explosive Limit: ND
Autoignition Temperature: > 600°F / 315°C Lower Explosive Limit: ND

Fire and Explosion Data:

Suitable Extinguishing Media: Halon, dry chemical, foam, CO₂, water mist or fog, or any Class B extinguishing agent

Products of Combustion: Fumes, smoke carbon monoxide

Explosion Hazards: Aerosol containers, when exposed to heat from fire, may build pressure and explode. Vapors may accumulate in a confined space and create a flammable atmosphere.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Methods for Containment & Clean-up: Dike area to contain spill. Eliminate all sources of ignition. Ventilate the area

Product Name: Cutting Oil Thread Cutting Lubricant (aerosol)

Product Number (s): 14050, 75500

with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Keep away from flames, sparks or hot surfaces. Wash thoroughly after handling and before handling food. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120°F / 49°C to prevent cans from rupturing.

Aerosol Storage Level: III

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

| COMPONENT | OSHA | | ACGIH | | OTHER | | UNIT |
|--|------|------|-------|------|-------|--------|-------------------|
| | TWA | STEL | TWA | STEL | TWA | SOURCE | |
| Hydrotreated naphthenic oil | 5* | NE | 5* | 10* | NE | | mg/m ³ |
| Additive blend | NE | NE | NE | NE | NE | | |
| Liquefied petroleum gas | 1000 | NE | 1000 | NE | NE | | ppm |
| N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated * – oil mist | | | | | | | |

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile or neoprene. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid (viscous)

Color: brown

Odor: faint petroleum

Odor Threshold: ND

Product Name: Cutting Oil Thread Cutting Lubricant (aerosol)**Product Number (s): 14050, 75500**

Specific Gravity: 0.924
 Initial Boiling Point: > 500°F / 260°C
 Freezing Point: ND
 Vapor Pressure: ND
 Vapor Density: > 5 (air = 1)
 Evaporation Rate: slow
 Solubility: negligible
 Coefficient of water/oil distribution: ND
 pH: NA
 Volatile Organic Compounds: wt %: 20.0 g/L: 184.8 lbs./gal: 1.54

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Sources of ignition

Incompatible Materials: Strong oxidizers, halogens

Hazardous Decomposition Products: Oxides of carbon, sodium, or sulfur. Aldehydes.

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

| <u>Component</u> | <u>Oral LD50 (rat)</u> | <u>Dermal LD50 (rabbit)</u> | <u>Inhalation LC50 (rat)</u> |
|-----------------------------|------------------------|-----------------------------|------------------------------|
| Hydrotreated naphthenic oil | > 5000 mg/kg | > 2000 mg/kg | 2.18 mg/L/4H |
| Additive blend | No data | No data | No data |
| Liquefied petroleum gas | No data | No data | No data |

Chronic Toxicity:

| <u>Component</u> | <u>OSHA Carcinogen</u> | <u>IARC Carcinogen</u> | <u>NTP Carcinogen</u> | <u>Irritant</u> | <u>Sensitizer</u> |
|-----------------------------|------------------------|------------------------|-----------------------|-----------------|-------------------|
| Hydrotreated naphthenic oil | No | No | No | S (mild) | No |
| Additive blend | No | No | No | Unknown | Unknown |
| Liquefied petroleum gas | No | No | No | No | No |

| | | |
|---------|----------|-----------------|
| E – Eye | S – Skin | R - Respiratory |
|---------|----------|-----------------|

Reproductive Toxicity: No information available
Teratogenicity: No information available
Mutagenicity: Hydrotreated naphthenic oil: Mutagenic index of less than 1.0
Synergistic Effects: No information available
Other: IARC has determined in reviewing cancer prevalence of exposed workers that the carcinogenic activity of refined oils is related to the severity of processing of the base oil. The base oils contained in this product have been highly refined to remove aromatics, thus reducing carcinogenic potential. IP346: DMSO < 3.0%

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this

Product Name: Cutting Oil Thread Cutting Lubricant (aerosol)

Product Number (s): 14050, 75500

product.

Ecotoxicity: hydrotreated naphthenic oil – 96 Hr LC50, Fathead minnow: >30,000 mg/L (static)

Persistence / Degradability: This product is not readily biodegradable.

Bioaccumulation / Accumulation: No information available

Mobility in Environment: No information available

Section 13: Disposal Considerations

Waste Classification: The dispensed liquid product is not a RCRA hazardous waste. (See 40 CFR Part 261.20 – 261.33). Empty aerosol containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground): Consumer Commodity, ORM-D

ICAO/IATA (air): Consumer Commodity, ID8000, 9

IMO/IMDG (water): Aerosols, UN1950, 2.1, Limited Quantity

Special Provisions: None

Section 15: Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

| | | |
|------------------------------------|-----------------------|-----|
| Section 311/312 Hazard Categories: | Fire Hazard | No |
| | Reactive Hazard | No |
| | Release of Pressure | Yes |
| | Acute Health Hazard | No |
| | Chronic Health Hazard | No |

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
None

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

Product Name: Cutting Oil Thread Cutting Lubricant (aerosol)

Product Number (s): 14050, 75500

Occupational Safety and Health Administration:

This product is regulated by the Hazard Communications Standard.

U.S. State Regulations:

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: None

Consumer Products VOC Regulations: This product is not compliant for use in the South Coast Air Quality Management District of California.

State Right to Know:

New Jersey: None
Pennsylvania: None
Massachusetts: None
Rhode Island: None

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: A, B5

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.


European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: None

Section 16: Other Information

| HMIS® (II) | |
|---------------|---|
| Health: | 1 |
| Flammability: | 1 |
| Reactivity: | 0 |
| PPE: | B |



Ratings range from 0 (no hazard) to 4 (severe hazard)

Prepared By: Michelle Rudnick
CRC #: 574
Revision Date: 01/23/2012

Changes since last revision: Section 15: VOC Regulations

Product Name: Cutting Oil Thread Cutting Lubricant (aerosol)

Product Number (s): 14050, 75500

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

| | |
|--|---|
| ACGIH: American Conference of Governmental Industrial Hygienists | NA: Not Applicable |
| CAS: Chemical Abstract Service | ND: Not Determined |
| CFR: Code of Federal Regulations | NIOSH: National Institute of Occupational Safety & Health |
| DOT: Department of Transportation | NFPA: National Fire Protection Association |
| DSL: Domestic Substance List | NTP: National Toxicology Program |
| g/L: grams per Liter | OSHA: Occupational Safety and Health Administration |
| HMIS: Hazardous Materials Identification System | PMCC: Pensky-Martens Closed Cup |
| IARC: International Agency for Research on Cancer | PPE: Personal Protection Equipment |
| IATA: International Air Transport Association | ppm: Parts per Million |
| ICAO: International Civil Aviation Organization | RoHS: Restriction of Hazardous Substances |
| IMDG: International Maritime Dangerous Goods | STEL: Short Term Exposure Limit |
| IMO: International Maritime Organization | TCC: Tag Closed Cup |
| lbs./gal: pounds per gallon | TWA: Time Weighted Average |
| LC: Lethal Concentration | WHMIS: Workplace Hazardous Materials Information System |
| LD: Lethal Dose | |